



VHF/UHF MULTIBAND FM TRANSCEIVER

IC-T90A

*Surprisingly compact, full featured tri-bander
with wideband receiver*

**5 Watts on 50MHz, 144MHz,
and 440MHz**

**Wideband receiver –
495kHz-999.990MHz!**

**555 alphanumeric memory
channels with Icom's
NEW DMS (Dynamic Memory Scan)
technology!**

Wideband receiver — 495kHz to 999.990MHz

The commercial grade IC-T90A transceiver offers a wideband AM, FM, and WFM scanning receiver. Not only you can hear your favorite TV programs with the pre-programmed TV memories, but also you can listen to shortwave, AM and FM broadcast radio stations with good sound quality. Police, fire, military, aircraft and various amateur bands also can be tuned.

DMS (Dynamic Memory Scan) bank scanning

With 555 alphanumeric memory channels, including 50 band edges and 5 call channels, Icom's DMS technology gives you flexible scanning lists. With a maximum of 18 banks or 100 channels per bank, you can pick and choose the desired channel for scanning from the 500 memories.

Lithium-Ion technology

Enjoy a full 5 watts from the supplied 1300mAh Lithium-Ion battery pack, BP-217. Along with the energy conserving settings, the BP-217 provides up to 5 to 6 hours*¹ of operating time and greatly reduces both the size and weight needed to get full output power. Just recharge and go!

*¹ Tx high: Rx: Stand-by duty ratio= 1: 1: 8

Rugged palm sized*², weather-resistant construction

This compact radio is comfortable in the smallest of hands, and offers full radio control for large fingers. The aluminum die-cast case and chassis is designed for the most rugged environments with weather resistance equivalent to JIS 4 specifications.

*² See back for actual dimensions.

DTCS and CTCSS tone squelch

A standard feature of the IC-T90A is both DTCS and CTCSS encode and decode capability. Choose from either 104 DTCS or 50 CTCSS codes for receive and transmit, individually. In addition, a pocket beep function gives you an audio alert when a matched tone signal is received — a great feature for quiet, group operations.

Simple operation

Simple, one-handed operation is the most valuable feature of the IC-T90A. The backlit ten-key pad allows you to enter frequency, memory number and set various other features. The tuning knob can be customized for either channel selection, or volume control.

Wait! There's more...

- DTMF encoder with 10 DTMF memories
- Auto squelch • Morse code synthesizer indicates the frequency in morse code
- Backlit LCD and keypad • High speed scanning • 13 scanning modes
- Antenna tip replaceable • PC Programmable
- 5.5–11V DC operation • Split operation
- Weather alert scan* (* U.S.A. version only)



Icom Inc.

SPECIFICATIONS

GENERAL

• Frequency coverage : (Unit: MHz)

Version	50MHz	144MHz	440MHz	Receive
U.S.A.	50-53.995	144-148	430-450**	0.495-999.990**2
Asia	50-53.995	144-148	430-440	0.495-999.990
General	50-53.995	144-148	430-440	0.495-999.990

** Guaranteed range 440-450. ** Cellular blocked.

- Mode : FM, AM (Rx. only), WFM (Rx. only)
- No. of memory Ch. : 555 (500 reg., 50 scan edges, 5 call)
- Frequency stability : ±6ppm (-10°C to +60°C)
- Useable temp. range : -10°C to +60°C; +14°F to +140°F
- Power supply : 5.5 to 11V DC or specified battery pack
- Current drain (at 8.0V DC):
 - Tx High : 2.0A typ.
 - Low : 0.8A typ.
 - Rx Rated audio : 220mA
 - Power save : 35mA (duty=1:4)
- Tuning steps (kHz) : 5, 6.25, 8.33, 9, 10, 12.5, 15, 20, 25, 30, 50, 100, 200
- Antenna impedance : 50Ω (SMA)
- Dimensions : 58(W)×87(H)×29(D) mm ; (projections not included) 2¹⁷/₃₂(W)×3⁷/₁₆(H)×1⁵/₃₂(D) in.
- Weight (approx.) : 240g; 8¹/₂ oz (w/antenna and BP-217)

TRANSMITTER

- Output power (8.0V DC): High 5W Low 0.5W
- Spurious emissions : Less than -60dB
- Max. freq. deviation : ±5.0kHz
- Ext. MIC connector : 3-conductor 2.5(d) mm (1/8")/2kΩ

RECEIVER

- Receive system : Double-conversion superheterodyne
- Intermediate freq. : 1st 69.45MHz (FM/AM)
13.350MHz (WFM)
2nd 450kHz
- Sensitivity* (typ., except spurious points):
 - FM : 1.625-4.995MHz 0.4μV
 - (at 12dB SINAD) : 5-49.995MHz 0.18μV
 - 50-54MHz 0.16μV
 - 54.005-143.995MHz 0.18μV
 - 144-148MHz 0.16μV
 - 148.005-221.995MHz 0.4μV
 - 222-225MHz 0.32μV
 - 225.005-246.995MHz 0.4μV
 - 247-429.995MHz 0.32μV
 - 430-450MHz 0.16μV
 - 450.005-832.995MHz 0.32μV
 - 833-999.990MHz 1.0μV

WFM (at 12dB SINAD)	40-108MHz	1μV
	175-221.995MHz	1.8μV
	470-770MHz	3.2μV
AM (at 10dB S/N)	0.495-4.995MHz	1.3μV
	5-29.995MHz	0.56μV
	118-136MHz	0.5μV
	222-229.995MHz	0.79μV
	320-329.995MHz	1μV

- Selectivity (except WFM) : More than 15kHz/-9dB
Less than 30kHz/-50dB
- Spurious and image rejection ratio: 50MHz : More than 60dB (half IF: 50dB, IF: 40dB)
144MHz : More than 60dB (half IF: 50dB)
440MHz : More than 50dB (IF: 60dB)
- Audio output power : 200mW typ. at 10% distortion/8Ω load (at 25°C)
- AF output impedance : 8Ω

Supplied accessories (*depending on version)

- Battery pack (BP-217)
- Wall charger*
- Antenna
- Swivel belt clip

All stated specifications are subject to change without notice or obligation.

OPTIONS

BATTERY PACK AND CASE

BP-216
R6 (AA)
batteries × 2



BP-217
Li-Ion
7.4V/1300mAh



BATTERY PACK/CASE	OUTPUT POWER	BATTERY LIFE
BP-216	0.1W typ.	-
BP-217	5W typ.	5 hrs. on 144/440MHz band 6 hrs. on 50MHz band

Battery life is approx. time; (Tx high: Rx: Stand-by=1: 1: 8)

BC-139 DESKTOP CHARGER



Rapidly charges battery pack BP-217. Charging time (approx.): 2 hours.

CP-19 CIGARETTE LIGHTER CABLE WITH NOISE FILTER



Allows you to operate the transceiver with 11V DC output through a cigarette lighter socket (12V). The connected battery pack is charged simultaneously.

LC-152A CARRYING CASE



Helps protect the transceiver from scratches, etc. Fits any battery pack.

SPEAKER-MICROPHONES



- HM-46 : Slim dimensions. Equipped with an earphone jack and transmit indicator.
- HM-75A : Allows you to remotely select operating channels, etc., according to cloning.
- HM-131 : Compact and durable body. Equipped with an earphone jack and a revolving clip.

HS-94 EARHOOK-HEADSET + VS-1 VOX/PTT CASE



- Flexible boom microphone and rotating earbud with a spring earhook. Allows you hands-free operation.
- HS-85 HEADSET is also available. Includes VOX, PTT, "one-touch PTT" (TOT).

HM-128 EARPHONE-MICROPHONE



Ideal for hands-free operation by clipping the Mic. with PTT switch to your lapel or breast pocket.

MB-83 SWIVEL BELT CLIP



Prevents accidental dropping from your belt.

AD-92SMA ANTENNA CONNECTOR ADAPTER
Allows you to connect a BNC-type antenna.

BC-110AR/DR WALL CHARGER
Regularly charges battery packs. The same as supplied with some versions.

CS-T90A CLONING SOFTWARE + OPC-478 CLONING CABLE
Provides quick and easy editing of memory channels, memory names and set mode contents, for local repeater frequencies, etc.

OPC-474 CLONING CABLE
Used for handheld-to-handheld data cloning.

SP-13 EARPHONE
Provides clear audio in noisy environments.

Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone : (425) 454-7619

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: (604) 952-4266 Fax: (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022
URL : <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: 09 274 4062 Fax: 09 274 4708
URL : <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, SPAIN
Phone: (93) 590 26 70 Fax: (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
URL : <http://www.icomuk.co.uk>

Icom France S.a

Zac de la Plaine, Rue Brindejonc des Moulinas
BP 5804, 31505 Toulouse Cedex, France
Phone: 561 36 03 Fax: 561 36 03 00
URL : <http://www.icom-france.com>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: (02) 2559 1899 Fax: (02) 2559 1874
URL : <http://www.asia-icom.com>

Beijing Icom Ltd.

1305, Wanshang Plaza, Shijingshan Road,
Beijing, China
Phone: (010) 6866 6337 Fax: (010) 6866 3553



Certificate Number Q14190

Icom Inc. (Japan), is an ISO9001 certification acquired company.

Your local distributor/dealer: